

FORM PTO-1390 (Modified) (REV 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER <b>5754-00007</b>	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR <b>10/030461</b>	
INTERNATIONAL APPLICATION NO. <b>PCT/JP00/04326</b>		INTERNATIONAL FILING DATE <b>June 30, 2000</b>		PRIORITY DATE CLAIMED <b>July 9, 1999</b>	
TITLE OF INVENTION  <b>MORTAR GROUTING TYPE JOINT FOR REINFORCING BARS</b>					
APPLICANT(S) FOR DO/EO/US  <b>Masahiro ABUKAWA</b>					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below.</li> <li>4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31).</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> <li>a. <input checked="" type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau).</li> <li>b. <input checked="" type="checkbox"/> has been communicated by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> <li>a. <input checked="" type="checkbox"/> is attached hereto.</li> <li>b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4).</li> </ol> </li> <li>7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau).</li> <li>b. <input type="checkbox"/> have been communicated by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</li> <li>d. <input type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).</li> <li>10. <input checked="" type="checkbox"/> An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).</li> <li>11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409).</li> <li>12. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210).</li> </ol>					
<p><b>Items 13 to 20 below concern document(s) or information included:</b></p> <ol style="list-style-type: none"> <li>13. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>14. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>15. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment.</li> <li>16. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment.</li> <li>17. <input type="checkbox"/> A substitute specification.</li> <li>18. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>19. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.</li> <li>20. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4).</li> <li>21. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).</li> <li>22. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail</li> <li>23. <input checked="" type="checkbox"/> Other items or information:</li> </ol>					
<p><b>International Application as Published</b>  <b>PCT Written Opinion</b>  <b>PCT Forms: 301,304,308 &amp; 332</b></p>					

531 Rec'd PCT 07 JAN 2002

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.101) <b>10/030461</b>		INTERNATIONAL APPLICATION NO. <b>PCT/JP00/04326</b>		ATTORNEY'S DOCKET NUMBER <b>5754-00007</b>	
--	--	---	--	---	--

24. The following fees are submitted: <b>BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5)) :</b> <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... <b>\$1040.00</b> <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$890.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$740.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$710.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$100.00</b> <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>CALCULATIONS PTO USE ONLY</b>	
<b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>\$890.00</b>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (c)).				<b>\$130.00</b>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	14 - 20 =	0	x \$18.00	\$0.00	
Independent claims	1 - 3 =	0	x \$84.00	\$0.00	
Multiple Dependent Claims (check if applicable).				<input type="checkbox"/>	\$0.00
<b>TOTAL OF ABOVE CALCULATIONS</b>				<b>=</b>	<b>\$1,020.00</b>
<input checked="" type="checkbox"/> Applicant claims small-entity status. See 37 CFR 1.27). The fees indicated above are reduced by 1/2.				<b>\$510.00</b>	
<b>SUBTOTAL</b>				<b>=</b>	<b>\$510.00</b>
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).				<b>\$0.00</b>	
<b>TOTAL NATIONAL FEE</b>				<b>=</b>	<b>\$510.00</b>
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).				<input type="checkbox"/>	<b>\$0.00</b>
<b>TOTAL FEES ENCLOSED</b>				<b>=</b>	<b>\$510.00</b>
				Amount to be:	\$
				refunded	\$
				charged	\$

a. ☒ A check in the amount of \$510.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 04-1131 A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.


**NOTE:** Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Laurence C. Begin

Dinnin & Dunn, P.C.  
 Top of Troy Building  
 755 West Big Beaver Road  
 Troy, Michigan 48084

  
 SIGNATURE

Laurence C. Begin  
 NAME

42,310  
 REGISTRATION NUMBER

January 7, 2002  
 DATE

10050461 10/030461  
531 Rec'd PCT 07 JAN 2002

IN THE UNITED STATES PATENT  
AND TRADEMARK OFFICE

Group Art Unit \_\_\_\_  
Examiner \_\_\_\_\_

MASAHIRO ABUKAWA

Serial No.

**PRELIMINARY  
AMENDMENT**

Filed January 7, 2002

For: MORTAR GROUTING TYPE JOINT FOR  
REINFORCING BARS /

January 7, 2002

Box PCT  
Asst. Commissioner For Patents  
Washington, D.C. 20231

Sir:

Please amend the above-identified application in the following manner:

IN THE CLAIMS

3. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein each of the pair of thin-walled members constituting the supporting protrusion (5) has an angle ridge line (7) sloping on both sides with the portion supporting the reinforcing bar (12) constituting the apex.

4. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the bolt hole (8) is situated between the supporting protrusion (5) and the opening cover (2).

5. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the bolt hole (8) is situated in the portion of the cylindrical body side wall facing to the supporting protrusion (5).

6. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein:

the distance between the reinforcing bar supporting portions (6) of the pair of thin-walled members is smaller than the diameter of the reinforcing bar (12); and

the distance between the reinforcing bar supporting portion (6) and the cylindrical body central axis is substantially equal to the radius of the circular hole (3) of the opening cover (2).

I hereby certify that this correspondence is being deposited with the U.S. Postal Service as Express Mail No. EV025142733US addressed to: Box PCT, Assistant Commissioner for Patents, Washington, D.C. 20231, on January 7, 2002. Name of person mailing: C. Gail Boes  
Signature: C. Gail Boes Date JAN. 7, 2002

7. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the bolt hole (8) is provided in the vicinity of the point at which the straight line passing through the midpoint between the reinforcing bar supporting portions (6) of the pair of thin-walled members and the central axis of the hollow cylindrical body intersects the inner wall of the hollow cylindrical body.

8. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the line segment connecting the contact points of each of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the pair of thin-walled members extending parallel to each other.

9. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the line segment connecting the contact points of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the opening cover (2) side of the hollow cylindrical body.

10. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the angle made by the line segment connecting contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the pair of thin-walled members being parallel to each other.

11. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the angle made by the line segment connecting the contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the both ends of the hollow cylindrical body.

12. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein the diameter of the circular hole (3) of the opening cover (2) is the same as the diameter of the reinforcing bar (12) inserted into the joint, or an appropriate clearance is provided between the circular hole (3) of the opening cover (2) and the reinforcing bar (12) inserted into the joint.

13. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein a seal member mounting portion is integrally attached to the outer side of the opening cover (2).

14. (amended) A mortar grouting type joint for reinforcing bars according to claim 1, wherein each of the facing surfaces of the pair of thin-walled members has a dip angle which facilitates the guiding of the reinforcing bar (12).

Preliminary Amendment

5754-00007

REMARKS

Applicant has amended the claims to eliminate multiple dependencies.

Favorable consideration of the present application, as amended herein, is courteously requested.

Applicant has calculated no additional fee due in connection with this paper. The Commissioner is authorized to charge any deficiencies or credit any overpayments to Deposit Account No. 04-1131. A duplicate copy of the first page of this transmittal is enclosed.


LCB/

Respectfully submitted,

Date

JANUARY 7, 2002

By



Dinnin & Dunn, P.C.  
Top of Troy Building  
755 West Big Beaver Road  
Troy, Michigan 48084

Laurence C. Begin  
Reg. No. 42310  
Phone (248) 362-2800  
FAX (248) 362-2864

**MARKED UP CLAIMS**

3. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [or 2], wherein each of the pair of thin-walled members constituting the supporting protrusion (5) has an angle ridge line (7) sloping on both sides with the portion supporting the reinforcing bar (12) constituting the apex.

4. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 3], wherein the bolt hole (8) is situated between the supporting protrusion (5) and the opening cover (2).

5. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 4], wherein the bolt hole (8) is situated in the portion of the cylindrical body side wall facing to the supporting protrusion (5).

6. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 5], wherein:

the distance between the reinforcing bar supporting portions (6) of the pair of thin-walled members is smaller than the diameter of the reinforcing bar (12); and

the distance between the reinforcing bar supporting portion (6) and the cylindrical body central axis is substantially equal to the radius of the circular hole (3) of the opening cover (2).

7. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 6], wherein the bolt hole (8) is provided in the vicinity of the point at which the straight line passing through the midpoint between the reinforcing bar supporting portions (6) of the pair of thin-walled members and the central axis of the hollow cylindrical body intersects the inner wall of the hollow cylindrical body.

8. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 7], wherein the line segment connecting the contact points of each of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the pair of thin-walled members extending parallel to each other.

9. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 7], wherein the line segment connecting the contact points of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the opening cover (2) side of the hollow cylindrical body.

10. (amended) A mortar grouting type joint for reinforcing bars according

to claim 1 [to 7], wherein the angle made by the line segment connecting contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the pair of thin-walled members being parallel to each other.

11. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 7], wherein the angle made by the line segment connecting the contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the both ends of the hollow cylindrical body.

12. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 11], wherein the diameter of the circular hole (3) of the opening cover (2) is the same as the diameter of the reinforcing bar (12) inserted into the joint, or an appropriate clearance is provided between the circular hole (3) of the opening cover (2) and the reinforcing bar (12) inserted into the joint.

13. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 12], wherein a seal member mounting portion is integrally attached to the outer side of the opening cover (2).

14. (amended) A mortar grouting type joint for reinforcing bars according to claim 1 [to 13], wherein each of the facing surfaces of the pair of thin-walled members has a dip angle which facilitates the guiding of the reinforcing bar (12).

3/PRTS

107030461  
531 Rec'd PCT 07 JAN 2002

## DESCRIPTION

### MORTAR GROUTING TYPE JOINT FOR REINFORCING BARS

#### TECHNICAL FIELD

The present invention relates to a mortar grouting type joint for reinforcing bars suitable for connection of reinforcing bars and, in particular, pre-assembled reinforcing bars and connection of horizontal reinforcing bars of precast reinforced concrete (hereinafter abbreviated as PC) members.

#### BACKGROUND ART

A mortar grouting type joint for reinforcing bars consists of a hollow cylindrical body. Reinforcing bars are inserted into it through the openings at its both ends, and the cylindrical body is filled with mortar to thereby accomplish a butt type connection between a pair of reinforcing bars. This type of joint, which is disclosed in Japanese Patent No. 1848027, etc., is widely used in practice.

Conventionally, this joint has been used in vertical main reinforcing bar connection between PC members. That is, after placing a lower PC member from whose upper surface the upper end portions of main reinforcing bars protrude upwards, an upper PC member in whose lower end portion are embedded mortar grouting type joints for reinforcing bars with the lower end portions of main



reinforcing bars inserted therein, is placed in such a manner that the above-described exposed reinforcing bars are accommodated in the embedded joints, and then the embedded joints are filled with mortar. This arrangement is advantageous in that the upper and lower PC members are connected to each other in a condition in which they are substantially in contact with each other, and that it is possible to connect a number of vertical reinforcing bars together simultaneously by a single process.

JP, A, 9-189097 discloses a mortar grouting type joint in which there is provided on the inner wall surface of a tubular sleeve a supporting protrusion perpendicularly to the central axis of the sleeve and in which a reinforcing bar is pressed against the supporting protrusion by a bolt screwed in through a bolt hole provided in the portion of the inner wall surface of the tubular sleeve facing to this supporting protrusion, thereby securing the reinforcing bar in position.

Recently, large diameter reinforcing bars have come to be generally used for shorter term of works and labor saving. As a result, mortar grouting type joints for reinforcing bars as disclosed in Japanese Patent No. 1848027, etc. are often used for so-called bare connection of reinforcing bars and, in particular, the bare connection of pre-assembled reinforcing bar structures. This is due to the fact that, as the reinforcing bar diameter increases, the reinforcing bar connecting means conventionally used in this

field (gas pressure welding, screw coupler system, etc.) deteriorate in reliability and lead to increased difficulty in operation, whereas the mortar grouting type joint for reinforcing bars involves no such problems even in the case of large diameter reinforcing bars.

In the case of the bare connection of pre-assembled reinforcing bar structures (which includes vertical connection and horizontal connection), there are a large number of pairs of reinforcing bars to be connected together. In the conventional connecting methods, the connection is impossible unless all of them are in a perfect coaxial relationship. Thus, after placing the reinforcing bar structure to be connected at a predetermined position with respect to the other reinforcing bar structure already installed, alignment has to be performed to effect coaxial adjustment for each of the large number of pairs of reinforcing bars, which involves a very difficult and time-consuming operation.

When effecting the connection by means of mortar grouting type joints, one end of each joint is attached to a reinforcing bar of the already installed reinforcing bar structure beforehand, and alignment is roughly performed between the reinforcing bars of the structure to be connected and those of the already installed structure. Then, the joints are pulled back to the side of the structure to be connected and the facing portions of the reinforcing bars of each pair are positioned at the center in the longitudinal direction (hereinafter simply referred to as the center) of the joint to thereby



the mortar cures.

Also, when the mortar grouting type joint for reinforcing bars having a supporting protrusion as disclosed in JP, A, 9-189097 is used for the connection of bare reinforcing bars, the following problem is involved: since the supporting protrusion is formed perpendicularly to the central axis of the sleeve, that is, formed along the inner periphery of the sleeve, the mortar flow along the sleeve central axis is hindered by the supporting protrusion when filling the sleeve with mortar, so that there is a large grouting resistance or space unfilled with mortar (void) is formed on the back side of the supporting protrusion, resulting in a deterioration in the reinforcing bar connecting performance of the joint.

#### DISCLOSURE OF THE INVENTION

In view of the above problems, it is an object of the present invention to provide a mortar grouting type joint for reinforcing bars which is particularly suitable for bare connection of reinforcing bar composites each consisting of a large number of reinforcing bars as in the case of pre-assembled reinforcing bar structures.

In accordance with the present invention, there is provided a mortar grouting type joint for reinforcing bars consisting of a hollow cylindrical body having an opening cover at an end, a bolt hole on the side wall, and a supporting protrusion on the inner

peripheral wall, adapted to support reinforcing bars with a bolt and the supporting protrusion, wherein the supporting protrusion consists of a pair of thin-walled members extending in parallel in the longitudinal direction of the hollow cylindrical body, and wherein the thin-walled member each have a ridge line sloping toward the above-described opening cover, with the portion of the thin-walled member supporting the reinforcing bar inserted through the opening cover constituting the apex.

In the above joint, it is desirable for the hollow cylindrical body to have an opening cover at both ends thereof, with a supporting protrusion supporting each reinforcing bar inserted through each opening cover being provided on both sides. Further, it is desirable for each of the pair of thin-walled members constituting the supporting protrusion to have an angle ridge line sloping on both sides with the portion supporting the reinforcing bar constituting the apex. Further, the bolt hole is situated between the supporting protrusion and the opening cover, and also situated in the portion of the cylindrical body sidewall facing to the supporting protrusion, which is preferable. Further, in the above-described joint, it is desirable that the distance between the reinforcing bar supporting portions of the pair of thin-walled members be smaller than the diameter of the reinforcing bar and that the distance between the reinforcing bar supporting portion and the cylindrical body central axis be substantially equal to the radius of the circular hole of

the opening cover. Further, it is desirable that the bolt hole be provided in the vicinity of the point at which the straight line passing through the midpoint between the reinforcing bar supporting portions of the pair of thin-walled members and the central axis of the hollow cylindrical body intersects the inner wall of the hollow cylindrical body.

In the joint of the present invention, the line segment connecting the contact points of each of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the pair of thin-walled members extending parallel to each other. Further, in the joint of the present invention, the line segment connecting the contact points of the pair of thin-walled members and the cylindrical body inner wall may be arranged perpendicularly to the thin-walled members, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions toward the opening cover side of the hollow cylindrical body. Further, in the joint of the present invention, the angle made by the line segment connecting contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members may constitute an acute angle, the pair of thin-walled members being parallel to each other. Further, in the joint of the present invention, the angle made by the line segment connecting the contact points of the pair of thin-walled members

and the inner wall of the hollow cylindrical body and by the thin-walled members may constitute an acute angle, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions toward the both ends of the hollow cylindrical body.

In the joint of the present invention, it is desirable that the diameter of the circular hole of the opening cover be the same as the diameter of the reinforcing bar inserted into the joint, or that an appropriate clearance be provided between the circular hole of the opening cover and the reinforcing bar inserted into the joint. Further, in the joint of the present invention, a seal member mounting portion may be integrally attached to the outer side of the opening cover. Further, in the joint of the present invention, it is desirable that each of the facing surfaces of the pair of thin-walled members has a dip angle which facilitates the guiding of the reinforcing bar at the ridge line portion.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1(a) and 1(b) are longitudinal sectional views showing the mortar grouting type joint for reinforcing bars of the present invention, in which part (a) shows an example thereof and part (b) shows another example thereof;

Fig. 2 is a cross-sectional view showing an example of the way a reinforcing bar is held by the mortar grouting type joint

for reinforcing bars of the present invention;

Figs. 3(a) and 3(b) are longitudinal sectional views showing the way supporting protrusion s are arranged longitudinally with respect to a joint, in which part (a) shows an example thereof and part (b) shows another example thereof;

Figs. 4(a) and 4(b) are schematic diagrams (cross-sectional views) showing the position of the bolt hole in the mortar grouting type joint for reinforcing bars of the present invention, in which part (a) shows an example thereof and part (b) shows another example thereof.

Fig. 5 is a longitudinal sectional partial view showing an example of a seal member mounting portion.

[Description of Reference Numerals] 1...joint main body, 2...opening cover, 3...circular hole, 4...annular protrusion, 5...supporting protrusion, 6...reinforcing bar supporting portion, 7...ridge line, 8...bolt hole, 9... inlet or outlet, 10...seal member mounting portion, 11...screw, 12...reinforcing bar, 13...bolt, 14...line segment connecting the contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body, 15...surface having an inclination angle that facilitates the guiding of the reinforcing bar, 16...midpoint between the reinforcing bar supporting portions of the pair of thin-walled members, 17...central axis of the hollow cylindrical body, 18...point at which the straight line passing through the





The reinforcing bar 12 inserted through the opening cover 2 is guided on the reinforcing guide surfaces 15 along the ridge lines 7 so as to be coaxial with the joint 1, enabling the reinforcing bar and the joint 1 to be easily arranged coaxially. Further, the supporting protrusion s 5 extend longitudinally in the hollow cylindrical member, so that, when grouting mortar, the supporting protrusion s 5 do not hinder the flow of mortar, and there is no fear that a void will be formed. The reinforcing bar arranged coaxially with the joint 1 is fixed to the joint 1 by the bolt 13. Since the reinforcing bar support portions 6 of the supporting protrusion s 5 serve as a support stand when the reinforcing bar is pressed by the bolt, it is possible to secure the reinforcing bar and the joint in position while maintaining them in the coaxial relationship.

Thus, as shown in Fig. 1, in the joint of the present invention, by providing the supporting protrusion s 5 for supporting the reinforcing bars 12a and 12b inserted through the opening covers 2 on the respective sides of the hollow cylindrical body, it is possible to easily arrange the two reinforcing bars respectively inserted through both ends of the hollow cylindrical body in a coaxial relationship and secure them in position. In this case, it is desirable for the supporting protrusion s 5 provided on either side of the hollow cylindrical body to be arranged at the corresponding positions in the periphery of the joint, i.e., installed such that

the supporting protrusion s 5 are longitudinally aligned in the same straight line. When providing the supporting protrusion s 5 on either side of the hollow cylindrical body, there is no particular restriction regarding the longitudinal positions of the supporting protrusion s 5. Usually, the supporting protrusion s are provided in each of the half bodies obtained by dividing the hollow cylindrical body in two by a plane passing the midpoint of the central axis thereof and perpendicular to the central axis.

Note that, on the inner wall surface of the joint, a plurality of annular protrusions 4 are provided to a certain depth from the opening covers 2. These annular protrusions 4 serve to intensify the engagement between the cured mortar and the inner wall surface to thereby enhance the connection performance of the joint. In the joint of the present invention, the configuration and the installation positions of the annular protrusions are selected so as not to hinder the supporting of the reinforcing bar by the supporting protrusion s and the edge of the circular hole. It is desirable to provide no annular protrusions 4 in the region between the supporting protrusion s provided at different longitudinal positions of the hollow cylindrical body. Further, in the side wall of the joint, there are usually provided a inlet and a outlet 9 to be used when grouting or discharging mortar.

In the joint of the present invention, when, as shown in Fig. 1(b), the configuration of the ridge lines 7 of the thin-walled

members constituting the supporting protrusion s 5a is an angle shape sloping on either side of the reinforcing bar supporting portion 6, the two reinforcing bars respectively inserted from the two ends of the joint can be arranged and secured in position in a coaxial relationship more easily as described below.

That is, when, in performing reinforcing bar connection, the joint is engaged with one reinforcing bar side (e.g., the reinforcing bar 12-a side (hereinafter referred to as side A), the reinforcing bar first comes into contact with the supporting protrusion s 5 (arranged on side A of the joint) sloping toward the side A opening cover 2 through which the reinforcing bar is first inserted, and is automatically guided toward the reinforcing bar supporting portions 6 while sliding on the pair of thin-walled members constituting the supporting protrusion s 5, until it is arranged coaxially with the joint on the supporting protrusion s 5 side of the joint. As the engagement further progresses, the above-described reinforcing bar comes into contact with the ridge line portion sloping on the opening cover 2 side of the supporting protrusion s 5 installed on the other side (side B which is opposite to side A) of the joint, and is automatically guided toward the reinforcing bar supporting portions 6 while sliding on the pair of thin-walled members constituting the supporting protrusion s 5, until it is arranged coaxially with the joint also on side B of the joint. Next, when the joint is engaged with the other

reinforcing bar (12-b) substantially aligned therewith, this reinforcing bar also becomes coaxial with the joint on both side A and side B thereof. Next, the joint is pulled back by its half length toward the first reinforcing bar, and the contact position between the two reinforcing bars is mated with the longitudinal central portion of the joint. By this single reciprocal movement of the joint, the two reinforcing bars can easily attain a coaxial relationship. Thereafter, the bolt 13 is threaded in to fasten the reinforcing bar to the joint, whereby it is possible to prevent the coaxial relationship from being disturbed by the coaxial adjustment operation of other reinforcing bar pairs. This effect can be achieved by the fact that the thin-walled members constituting the supporting protrusion s have an angle shape ridge line sloping on both sides of the joint.

As shown in Fig. 3(a), in the joint of the present invention, the pair of thin-walled members 5 may extend parallel to each other, or the distance between the pair of thin-walled members 5 may continuously increase from the reinforcing bar supporting portion 6 toward the opening cover 2 side through which the reinforcing bar thereby supported is inserted. In addition, in the latter case, as shown in Fig. 3(b), the distance between the pair of thin-walled members 5 may continuously increase from the reinforcing bar supporting portion 6 toward the opening covers 2 at either end of the hollow cylindrical body. In either of the above-described cases,

the thin-walled members 5 may, as shown in Fig. 4(a), be arranged perpendicularly to the line segment 14 connecting the contact points of the thin-walled members and the inner wall of the hollow cylindrical member, or, as shown in Fig. 4(b) they may make an acute angle with the above-described line segment 14.

By arranging the pair of thin-walled members 5 such that the distance between them continuously increases from the reinforcing bar supporting portion 6 toward the opening cover 2 at one or both ends of the hollow cylindrical member, it is possible to guide the reinforcing bar more smoothly toward the reinforcing bar supporting portion 6. Also, when the thin-walled members are arranged perpendicularly to the above-mentioned line segment 14, the releasing from the joint mold equipped with supporting protrusion s is advantageously facilitated.

In the joint of the present invention, from the viewpoint of appropriately supporting the reinforcing bar by the supporting protrusion s, it is desirable that the distance between each of the reinforcing bar supporting portions 6 of the pair of thin-walled members constituting the supporting protrusion s be set smaller than the diameter of the circular hole 3 of the opening cover 2, that is, the diameter of the reinforcing bar. Further, from the viewpoint of arranging and fixing the reinforcing bar and the joint coaxially, it is desirable that the distance from the reinforcing bar supporting portion 6 of each thin-walled member to the central

axis of the hollow cylindrical body be substantially equal to the radius of the circular hole 3 of the opening cover 2, that is, the radius of the reinforcing bar. Further, to smoothen the guiding of the reinforcing bar by the supporting protrusion s 5 and to strengthen the support of the reinforcing bar by the supporting protrusion s 5, it is desirable that the opposing surfaces of the pair of thin-walled members be formed as surfaces 15 having an inclination angle facilitating the guiding of the reinforcing bar as shown in Figs. 2, 4, etc.

In the present invention, from the viewpoint of fixing the reinforcing bar and the joint in a stable manner, it is desirable that the bolt hole 8 be provided at a position between the supporting protrusion s 5 and the opening cover 2 through which the reinforcing bar supported by the supporting protrusion s 5 is inserted and in the portion of the side wall of the hollow cylindrical body facing to the supporting protrusion s 5, as shown in Figs. 1 and 2. Thus, of the two halves obtained by dividing the joint by a plane passing through the central axis of the hollow cylindrical body and parallel to the line segment 14 connecting the contact points of the pair of thin-walled member 5 and the inner wall of the hollow cylindrical body, one half has the supporting protrusion s 5, and the other half has the bolt hole 8. More preferably, the bolt 8 is provided, as shown in Fig. 4, in the vicinity of a point 18 where the straight line passing through the midpoint 16 between the reinforcing bar

supporting portions 6 of the pair of thin-walled members 5 and the central axis 17 of the hollow cylindrical body intersects the inner wall of the hollow cylindrical body.

From the viewpoint of fixing the reinforcing bar and the joint coaxially by supporting the reinforcing bar by the supporting protrusion 5, the bolt, and the edge of the opening cover 2, it is desirable, in the joint of the present invention, that the diameter of the cylindrical hole 3 of the opening cover 2 be the same as the diameter of the reinforcing bar inserted into the joint. Taking the ease with which the reinforcing bar is inserted into the joint into consideration, it is possible to provide an appropriate clearance between the circular hole 3 of the opening cover 2 and the reinforcing bar inserted into the joint.

When grouting the joint with mortar, mortar will leak through the gap between the circular hole of the opening cover of the joint and the inserted reinforcing bar, so that it is necessary to seal the gap. Fig. 6 shows a joint equipped with a seal member mounting portion 10. The seal member mounting portion 10 consists of a cylindrical portion formed by extending the side wall of the joint main body 1 outside the opening cover 2 so as to be integral with the joint, the opening cover 2 constituting the bottom thereof. The seal member consists of a cylindrical member formed of rubber or the like and having at its center a reinforcing bar passing hole, a screw being provided on the side wall thereof. In the inner wall



of the seal member mounting portion, there formed is a screw 11 adapted to be threadedly engaged with the above-mentioned screw, the seal member being attached to the joint through threaded engagement. While the seal member mounting portion is normally provided at both ends of the joint, it is possible to provide it only at one end in the case of vertical connection.

While for the sake of convenience the present invention has been described above as applied to the case in which reinforcing bar structures are connected, the mortar grouting type joint for reinforcing bars of the present invention can also be used for the connection of the horizontal main reinforcing bars of PC members. In this case, both of the main reinforcing bars to be connected stick out horizontally and are exposed, the joint being first engaged with one main reinforcing bar side, and then horizontal alignment of the other main reinforcing bar being effected. Thereafter, the same operation as described above is conducted.

#### INDUSTRIAL APPLICABILITY

When performing connection of a number of sets of bare reinforcing bars or when performing connection of the horizontal main reinforcing bars of the PC members, the mortar grouting type joint for reinforcing bars of the present invention provides the following advantages over the conventional mortar grouting type joint for reinforcing bars.

(1) The operation of adjusting the coaxial relationship of a number of pairs of reinforcing bars can be executed easily and quickly, thereby achieving a substantial improvement in terms of operational efficiency.

(2) The reinforcing bars can be secured in position easily and reliably until the mortar is grouted and the grouted mortar cures. Further, the resistance when grouting the joint with mortar is small, thereby achieving a reduction in operational time, simplification of operation, and a further improvement in operational efficiency.

(3) It is possible to make the difference in diameter between the circular hole of the opening cover and the reinforcing bar as small as possible, thereby making the diameter of the joint smaller and achieving an improvement in design fitness.

(4) Since it is possible to prevent void formation as a result of mortar grouting, there is no deterioration in the reinforcing bar connecting performance of the joint. Further, the reliability of the reinforcing bar connecting portion is improved, thereby achieving an improvement in the quality and safety of the reinforced concrete building.

# CLAIMS

1. A mortar grouting type joint for reinforcing bars, comprising a hollow cylindrical body having an opening cover (2) at an end, a bolt hole (8) on the side wall, and a supporting protrusion (5) on the inner peripheral wall, adapted to support reinforcing bars (12) with a bolt (13) and the supporting protrusion (5), wherein:

the supporting protrusion (5) consists of a pair of thin-walled members extending in parallel in the longitudinal direction of the hollow cylindrical body; and

said thin-walled members each have a ridge line (7) sloping toward the opening cover (2), with the portion of the thin-walled member supporting the reinforcing bar (12) inserted through the opening cover (2) constituting the apex.

2. A mortar grouting type joint for reinforcing bars according to claim 1, wherein the hollow cylindrical body has an opening cover (2) at both ends thereof, with a supporting protrusion (5) supporting each reinforcing bar (12) inserted through each opening cover being provided on both sides.

3. A mortar grouting type joint for reinforcing bars according to claim 1 or 2, wherein each of the pair of thin-walled members constituting the supporting protrusion (5) has an angle ridge line

(7) sloping on both sides with the portion supporting the reinforcing bar (12) constituting the apex.

4. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 3, wherein the bolt hole (8) is situated between the supporting protrusion (5) and the opening cover (2).

5. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 4, wherein the bolt hole (8) is situated in the portion of the cylindrical body side wall facing to the supporting protrusion (5).

6. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 5, wherein:

the distance between the reinforcing bar supporting portions (6) of the pair of thin-walled members is smaller than the diameter of the reinforcing bar (12); and

the distance between the reinforcing bar supporting portion (6) and the cylindrical body central axis is substantially equal to the radius of the circular hole (3) of the opening cover (2).

7. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 6, wherein the bolt hole (8) is provided in the vicinity of the point at which the straight line passing

through the midpoint between the reinforcing bar supporting portions (6) of the pair of thin-walled members and the central axis of the hollow cylindrical body intersects the inner wall of the hollow cylindrical body.

8. Amortar grouting type joint for reinforcing bars according to any one of claims 1 to 7, wherein the line segment connecting the contact points of each of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the pair of thin-walled members extending parallel to each other.

9. A mortargrouting type joint for reinforcing bars according to any one of claims 1 to 7, wherein the line segment connecting the contact points of the pair of thin-walled members and the cylindrical body inner wall is arranged perpendicularly to the thin-walled members, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the opening cover (2) side of the hollow cylindrical body.

10. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 7, wherein the angle made by the line segment connecting contact points of the pair of thin-walled

members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the pair of thin-walled members being parallel to each other.

11. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 7, wherein the angle made by the line segment connecting the contact points of the pair of thin-walled members and the inner wall of the hollow cylindrical body and by the thin-walled members constitute an acute angle, the distance between the pair of thin-walled members increasing continuously from the reinforcing bar supporting portions (6) toward the both ends of the hollow cylindrical body.

12. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 11, wherein the diameter of the circular hole (3) of the opening cover (2) is the same as the diameter of the reinforcing bar (12) inserted into the joint, or an appropriate clearance is provided between the circular hole (3) of the opening cover (2) and the reinforcing bar (12) inserted into the joint.

13. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 12, wherein a seal member mounting portion is integrally attached to the outer side of the opening

cover (2).

14. A mortar grouting type joint for reinforcing bars according to any one of claims 1 to 13, wherein each of the facing surfaces of the pair of thin-walled members has a dip angle which facilitates the guiding of the reinforcing bar (12).

# ABSTRACT

A mortar grouting type joint for reinforcing bars is provided, which comprises a hollow cylindrical body having an opening cover (2) at an end, a bolt hole (8) on the side wall, and a supporting protrusion (5) on the inner peripheral wall, adapted to support reinforcing bars (12) with a bolt (13) and the supporting protrusion (5), wherein the supporting protrusion (5) consists of a pair of thin-walled members extending in parallel in the longitudinal direction of the hollow cylindrical body, and each thin-walled member has a ridge line (7) sloping toward the opening cover (2), with the portion of the thin-walled member supporting the reinforcing bar (12) inserted through the opening cover (2) constituting the apex, whereby the reinforcing bar to be inserted can be automatically guided to the position coaxial with the joint, said joint being suitable for performing connection of a number of sets of bare reinforcing bars such as connection of reinforcing bar structures.



Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5



10030461 10411112  
PCT 336

PTO/SB/01 (10-01)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)</b>  <input type="checkbox"/> Declaration Submitted with Initial Filing      OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Attorney Docket Number</b>	
	<b>First Named Inventor</b>	ABUKAWA
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	/
	<b>Filing Date</b>	
	<b>Art Unit</b>	
	<b>Examiner Name</b>	

**As the below named inventor, I hereby declare that:**

My residence, mailing address, and citizenship are as stated below next to my name

I believe I am the original and first inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**MORTAR GROUTING TYPE JOINT FOR REINFORCING BARS***(Title of the Invention)*

the specification of which

☐ is attached hereto

OR

☒ was filed on (MM/DD/YYYY) **June 30, 2000** as United States Application Number or PCT InternationalApplication Number **PCT/JP00/04326** and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent, inventor's or plant breeder's rights certificate(s), or any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
1999-195689	Japan	07-09-99	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 21 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

## DECLARATION — Utility or Design Patent Application

Direct all correspondence to: ☐ Customer Number or Bar Code Label  OR ☒ Correspondence address below

Name **Dinnin & Dunn, P.C.**

Address **755 West Big Beaver Rd. Suite 2100**

City **Troy**

State **MI**

ZIP **48084**

Country **U. S. A.**

Telephone **(248) 362-2800**

Fax **(248) 362-2864**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF SOLE OR FIRST INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any)) **Masahiro**

Family Name or Surname **ABUKAWA**

Inventor's Signature *M. Abukawa*

Date *December 21, 2001*

Residence: City **Koshigaya**

State **Saitama**

Country **Japan**

Citizenship **Japan**

Mailing Address **JPX**

City **Koshigawa**

State **Saitama**

ZIP **343-0807**

Country **Japan**

NAME OF SECOND INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))

Family Name or Surname

Inventor's Signature

Date

Residence: City

State

Country

Citizenship

Mailing Address

City

State

ZIP

Country

☐ Additional inventors are being named on the \_\_\_\_\_ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto